Patterns to Ease the Port of Micro-kernels in Embedded Systems

Michel de Champlain

Department of Computer Science
University of Canterbury, Christchurch, New Zealand
michel@cosc.canterbury.ac.nz

July 29, 1996

Abstract

Micro-kernels are difficult to port to a new hardware platform. During the initial phases of a port, much time and effort is lost on debugging critical machine-dependent subsystems. These subsystems are generally very tightly coupled and cannot be tested in an incremental fashion. Tight coupling occurs because the subsystems share many global variables forcing them to be debugged with the complete micro-kernel's code. The problem of porting and testing new micro-kernel ports has so far received little attention, and the work described in this paper is an attempt to fill this gap.

A typical design pattern captures and communicates the development and reuse of objects and their interaction in a specific context. In the embedded domain, we have found design patterns very useful to encapsulate requests, to decouple subsystems, and to make policies interchangeable. Our patterns are more than objects that work together to solve a design problem, they are also patterns for organizing other patterns to address the testing and porting issues.

We describe the design and implementation of various object-based design patterns which address the problem of the initial porting of micro-kernels for embedded systems in a systematic and incremental fashion using bottom-up integration testing. The motivation behind our design patterns is presented along with an outline of their consequences, constraints and applicability to the port. In the course of several iterations, these patterns have been tested and refined through their use in porting of an existing embedded micro-kernel to different hardware platforms.

Keywords: Design patterns, embedded systems, micro-kernel initial port, bottom-up testing, object-based programming.

1 Introduction

An important concern in the development of micro-kernels is their portability across different hardware platforms. Most micro-kernel subsystems, including the machine-dependent ones, are written in high level languages such as C [1, 2], C++ [3], and Modula-3 [4]. As a result, very little machine-dependent assembly code needs to be rewritten for each new port.

Even so, the design and implementation of portable micro-kernels to run on different computer architectures, such as Mach [5], V [6] and Chorus [7], are serious challenges [8, 2]. In particular the debugging phase of a micro-kernel port is still considered black magic and an art, especially for machine-dependent subsystems that are time consuming and require exhaustive testing.

Even if the micro-kernel's code is readable and easy to maintain, the initial port to a new machine demands a significant effort since this phase is generally tested monolithically. In spite of the careful modularisation some critical machine-dependent subsystems, such as the real-time clock, the context switch and the scheduler, are very hard to debug and test.

A micro-kernel port needs to be tested in a more systematic and incremental fashion, we have used these patterns during several micro-kernel design and implementation allowing each critical component to be fully tested. This paper describes the *object manager*, *timer*, and *scheduler* patterns we have adopted and their applicability. We have implemented and used these patterns for several ports. While our work occurs in the context of embedded systems, we believe our approach will be also useful to port general purpose micro-kernels across different processors in a more systematic and rapid manner.

This paper is organised as follows. Section 2 briefly describes the overall development life cycle and architecture of our patterns, and the context in which this work has been done. Section 3 introduces each individual pattern and their respective objects. Section 4 examines and comments on related issues and finally, section 5 presents a brief evaluation, future plans, and some conclusions.

2 The Overall Approach

This section describes the overall development life cycle and architecture of our machine-dependent patterns for the port of micro-kernels in embedded systems.

Context The long term objective of our projects [9, 10, 11, 12] was to simplify the porting of micro-kernels for embedded applications. By this we mean that patterns will encapsulate hardware features and will be part of an effective testing process.

Problem Micro-kernels are difficult to port to a new hardware platform. Good encapsulation is not enough to eliminate all problems during an initial port. Without methodical and incremental tests some non-trivial machine-dependent objects such as the real-time clock, the context switch and the scheduler can be extremely time consuming to debug.

Motivation Our main motivation was not to discover objects for reuse but to develop patterns which promote portability (with greater ease) across different platforms. These problems force us to design, implement and further enhance frameworks to provide a more systematic porting procedure. After several iterations we found that our design requirements were very compatible with the object-oriented (OO) paradigm. It is worthwhile to note that previous work has already demonstrated the advantage of OO design for micro-kernels [2]. But our work refines on a missing portability issue: capturing and describing patterns which contribute to the initial phases of a micro-kernel port.

Embedded soft real-time[1] systems must satisfy timing constraints [13] in which a micro-controller is usually interfaced directly to some physical equipment and is dedicated to monitoring the operation of that equipment [14]. Most of these embedded systems have restricted (volatile and non-volatile) memory space requirements. Fuel injection systems, washing machines and mobile radio systems for remote site monitoring and control are typical examples. In this domain of applications the use of the full spectrum of OO techniques is sometimes difficult. The reasons induct overhead in code and memory space; and possible non-deterministic behavior of unexpected creation and deletion of objects, dynamic binding, etc. Instead we are using object-based techniques as a trade-off to be

[1] A soft real-time requirement is characterized by an average response time, e.g. a request that must be satisfied on average.